

**KILOVAC MAP201 Series Contactor with 2 Form A (SPST-NO)
Contacts Rated up to 350 Amps, 12-900 Vdc Dual Contact Material (Cu/Mo)**

Product Facts

- Designed to be the smallest, lightest weight, lowest cost sealed contactor in the industry with its current rating for military aerospace
- Built-in coil economizer (models requiring external economizer also available)
- Optional auxiliary contact for easy monitoring of power contact position
- Hermetically sealed — intrinsically safe, operates in explosive/harsh environments with no oxidation or contamination of coil or contacts, including long periods of non-operation
- Versatile coil and power connections



Physical Data

Contact Arrangement —

Power Contacts — SPST-NO (form X)
2X Auxiliary Contacts 1 — SPST-NO (form A)

Dimensions — See drawing

Weight, Nominal — 0.45 Kg (0.99 lb)

Environmental Data

Shock, 11ms 1/2 Sine (Operating) — 20 G_{peak}

Sine Vibration, 20 G_{peak} — 55-2000 Hz

Random Vibration, 14.06 Grms — 15 Hz (.002 G²/Hz), 100 Hz (.002 G²/Hz), 450 Hz (.12 G²/Hz), 900 Hz (.12 G²/Hz), 2000 Hz (.083 G²/Hz)

Operating Temperature Range — -55°C to +85°C

Electrical Data

Voltage Rating — Main Contacts (max) — 400 Vdc
Auxiliary Contacts — 30 Vdc

Current Rating, Continuous — Main Contacts 2 — 300 A
Auxiliary Contacts — 3 A

Contact Resistance — Main Contacts 3 — 100 mΩ max @ 1 amp
0.3 mΩ max @ rated current
Auxiliary Contacts — 200 mΩ max

Hot Switching Performance (Polarity Sensitive) — 600A make/ 265A break @ ± 270Vdc — 11,000 cycles
550A make/ break @ ± 360Vdc — 100 cycles
2000A capacitive make — 100 cycles
2000A make/ break @ +360Vdc — 5 cycles
1000A make/ break @ -360Vdc — 2 cycles

Mechanical Life — 100,000 cycles

Dielectric Withstand Voltage — Terminal to Terminal/ Terminals to Coil — 1mA max @ 2,200Vrms

Coil Data

Coil Voltage, Nominal/ Max — 28/ 32 Vdc

Pick Up (Max) — 16 Vdc

Inrush Current @ 28Vdc (Max) — 3.5 A

Inrush Time (Max) — 100 ms

Hold Current (Max) — 0.32 A

Drop Out — 4 to 10 Vdc

Main Contacts —

Operate Time (Max) — 18 ms

Operate Bounce (Max) — 5 ms

Release Time — 18 ms

Auxiliary Contacts Operate/ Release — Within ± 5 ms of main

Insulation Resistance —

Terminal to Terminal/ Terminals to Coil — 100MΩ min @ 500Vdc

Notes:

- 1 Two form A available with electronic coil economizer, 1 form A available with mechanical coil economizer
- 2 Continuous current rating is affected by conductors attached. Keep terminals below 150°C max continuous, 175C for 1 hour max, and 200C for 1 minute max.
- 3 Initial contact resistance may be higher than 0.3mΩ, but will drop below within 30 minutes maximum

Ordering Information

Typical Part Number ►

MAP201 A R D E A

Series: _____
MAP201 = 350 Amp, 12-900VDC Contactor

Contact Form: _____
A = Normally Open
H = Normally Open with Aux. Contacts

Coil Voltage: _____
R = 28 Vdc, Mechanical Economizer
S = 28 Vdc, Electrical Cut-throat Economizer

Coil Wire Length: _____
A = 15.3 in (390 mm)
D = Coil connector on relay (requires option "E" or "X" in next step).


Coil Terminal Connector: _____
N = No connector
E = 9-pin subminiature "D" plug mounted on contactor housing
X = Special configuration (consult factory)

Mounting & Power Terminals: _____
A = Bottom Mount & Male M8 x 1.25 Thread Terminals
B = Bottom Mount & Female 1/4-20 Thread Terminals
D = Bottom Mount & Female M6 x 1 Thread Terminals

For factory-direct application assistance, dial 800-253-4560, ext. 2055, or 805-220-2055.

KILOVAC MAP201 Series Contactor (Continued)

Outline Dimensions*



**MAP200HR D-Sub
Pin Out**

Coil+ = Pin 2
Coil - = Pin 6
Aux. COM = Pin 8
Aux. NO = Pin 4

MAP200AR

Coil+ = Pin 2
Coil - = Pin 6

***Alternate coil and main terminal connections available, consult factory.**

For factory-direct application assistance, dial 800-253-4560, ext. 2055, or 805-220-2055.